



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

I also certify that the attached copy of the request for grant of a Patent (Form 1/77) bears an amendment, effected by this office, following a request by the applicant and agreed to by the Comptroller-General.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 26 June 2003

OLIFF & BERRIDGE, PLC

P.O. BOX 19928

ALEXANDRIA, VA 22320

(703) 836-6400

APPLICANT: Andrew Charles RENSHAW

APPLICATION NO.: New U.S. Application

FILED: October 21, 2003

FOR: CROSS BRACE CLAMP ASSEMBLY

ATTORNEY DOCKET NO.: 116665

THE PATENT OFFICE

14 NOV 2002

NEWPORT

14NOV02 E763384-4 D02835
P01/7700 0.00-0226540.3

The Patent Office

Cardiff Road, Newport
South Wales NP9 1RH

Request for grant of a patent

(see the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference P650948GB

2. Patent application number
(The Patent Office will fill in this part) 0226540.3 14 NOV 2002

3. Full name, address and postcode of the or of each applicant (underline all surnames)
RENTHAL LIMITED
BREDBURY PARK WAY
BREDBURY
STOCKPORT SK6 2SN

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

GB

6837850001

4. Title of the invention HANDLEBAR CROSSBRACE CLAMP ASSEMBLY

5. Name of your agent (if you have one) ~~URQUHART-DYKES & LORD~~ Harrison Goddard Foot
"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode) ~~GREG'S BUILDINGS~~ Orlando House
~~1 BOOTH STREET~~ 116 Conyshall Road
~~MANCHESTER~~ Maple Bridge
~~M2 4DU~~ STOCKPORT
SK6 5HH

Patents ADP number (if you know it)

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country	Priority application number (If you know it)	Date of filing (day/month/year)
---------	---	------------------------------------

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application	Date of filing (day/month/year)
-------------------------------	------------------------------------

8. Is a statement of inventorship and or right to grant of a patent required in support of this request? (Answer "Yes" if:)
a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant, or
c) any named applicant is a corporate body;
see note (d)

YES

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document

Continuation sheets of this form -

Description 9

Claim(s) 2

Abstract -

Drawing(s) 2 + 2

- 10 If you are also filing any of the following items state how many against each item:

Priority documents -

Translation of priority documents -

Statement of inventorship and right to grant of a patent (patents form 7/77)

2 COPIES ✓

Request for preliminary examination and search (patents form 9/77)

1 ✓

Request for substantive examination (patents form 10/77)

-

Any other documents (please specify) -

11

I/We request the grant of a patent on the basis of this application.

Signature

Date 13/11/02

Urquhart-Dykes & Lord

URQUHART-DYKES & LORD

- 12 Name and daytime telephone number of person to contact in the United Kingdom

R A BARKER 0161 832 9353

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patent Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- if you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered "Yes" Patents Form 7/77 will need to be filed
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

**Statement of inventorship and of
right to grant of a patent**

THE PATENT OFFICE

14 NOV 2002

NEWPORT

The Patent Office

Cardiff Road, Newport
South Wales NP9 1RH

1. Your reference

P650948GB

2. Patent application number
(If you know it)

0226540.3

14 NOV 2002

3. Full name of the or of each applicant

RENTHAL LIMITED

4. Title of the invention

HANDLEBAR CROSSBRACE CLAMP ASSEMBLY

5. State how the applicant(s) derived the right
from the inventor(s) to be granted a patent

BY VIRTUE OF SECTION 39(1) OF THE PATENTS ACT
1977, THE INVENTOR BEING AN EMPLOYEE OF THE
APPLICANT.

6. How many, if any additional Patents Form 7/77
are attached to this form?
(see note (c))

1 COPY

7.

I/We believe that the person(s) named over the page (and on any
extra copies of this form) is/are the inventor(s) of the invention
which the above patent application relates to:

Signature *Urquhart-Dykes & Lord* Date 13/11/02

URQUHART-DYKES & LORD

8. Name and daytime telephone number of
person to contact in the United Kingdom

R A BARKER 0161 832 9353

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form
- When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant
- Once you have filled in the form you must remember to sign and date it.

Enter the full names, addresses and postcode of the inventors in the boxes and underline the surnames

ANDREW CHARLES RENSHAW
CLARKE HOUSE
KISKHILL LANE
RAINOW
MACCLESFIELD
CHESHIRE
SK10 5UR

Patent ADP number (if you know it) 6837876002

Patent ADP number (if you know it)

Reminder

Have you signed the form?

Patent ADP number (if you know it)

- P650948GB -

HANDLEBAR CROSSBRACE CLAMP ASSEMBLY

This invention concerns an arrangement for clamping respective ends of a crossbrace to a handlebar, particularly but not exclusively a motorcycle handlebar.

Cross braces in the form of metal rods are fitted to motorcycle handlebars of a particular, well known configuration involving four bends, as shown in Figure 1. Each bar 20 has a central section 10, which in use will be clamped onto the bike at a central location, respective end sections 12, 14, which in use will be at a higher level than the central section 10 and to the ends of which hand grips and controls will be fitted, and respective intermediate or bent sections 16, 18, which extend between the central section 10 and each end section 12, 14. The bar 20 is first bent at each end of the central section 10, leading into the proximal end of the respective bent section 16, 18, and is bent again at the distal end of each bent section, leading into the respective end section 12, 14. The bar 20 is symmetrical, the two end sections 12, 14 lying on a common axis. Such bars are invariably tubular, and of steel or aluminium, but that is not essential to the invention.

Conventional bars of this shape have a substantially constant external diameter ($\frac{7}{8}$ ", namely 22.23mm).

A crossbrace 21 is fitted between the respective bent sections 16, 18, for enhanced strength and rigidity. It is attached by a clamp (22 or 24) at each end. Two forms of clamp are known for this purpose.

The older form comprises a pair of C shaped clamp elements, each having a pair of opposed connection straps, which are bolted together in a facing disposition, with a bolt at each side of the handlebar. One of these bolts also secures the end of cross brace, which is formed into a flattened tongue or lug.

Because one of the bolts and the connection straps it secures projects inconveniently for motocross cycle riders, who need to be able to turn the handlebar right into the body in some instances, the aforesaid clamp has been superceded, at least on motocross bikes and the like, by a single U-shaped clamp body (22 or 24) which partially encircles the bar. This clamp 24 is generally secured by a single bolt 26, which also secures the end of the crossbrace 21, as shown in Figure 2, which is again formed into a flattened tongue or lug 29. Alternatively, as shown in Figure 1, such a clamp 22 may have elongate clevis arms and be secured by two bolts 23, 25, one of which secures the clamp body 22 to the bar 20, and the other of which secures

the end of the crossbrace 21 to the clamp body 22, as described in US 5,064,157.

Motorcycle handlebars are now known, as described, for example, in US 5,117,708, US 5,257,552, and US 5,950,497, which are of similar overall configuration, but wherein the external diameter of the central section is enlarged (to 1 $\frac{1}{8}$ " , namely 28.58mm) and the bent sections taper from their proximal ends, at or near the central section, to their distal ends, at or near the end sections, which remain at an external diameter of about $\frac{7}{8}$ " (22.23mm). Hitherto, such handlebars have not been fitted with crossbraces. They already have enhanced strength compared to the constant but smaller external diameter bars.

It is now desired to fit crossbraces to these latter bars, but it is difficult, with the style of clamps known hitherto, to clamp a tapering frustoconical surface so that there will be no slippage and simultaneously clamp the end of a crossbrace, bearing in mind that it is also important to have a wide area of contact between the bar and the clamp to minimise the risk of uneven wear or uneven stress leading to failure of the bar, and risk to life.

An object of the present invention is to provide a crossbrace clamp assembly which is suitable for fitting to tapered handlebars as aforesaid, bearing in mind safety requirements, and which is relatively easy to fit thereto.

A further object is to provide a crossbrace clamp assembly which can be fitted to different sizes of tapered handlebars, without the need for a range of different sizes of crossbrace. In this respect most manufacturers of such handlebars provide from two to six different sizes of bars where the bent sections are of slightly differing length or inclination, to suit different statures and personal preferences of riders.

It must be stressed that although the crossbrace clamp assembly according to the invention, has been devised in order to meet the above object for tapered handlebars, it can also be used on handlebars of substantially constant external diameter.

Yet a further object of the invention is to provide a crossbrace clamp assembly which is sufficiently easy to fit and is sufficiently secure when clamped to the bar as not to require additional securement of the clamps by adhesive that it can be removed, replaced, re-fitted, or transferred between bars subsequent to original manufacture or assembly of the bar.

An assembly in accordance with the invention, which fulfils these objectives, comprises crossbrace which is formed at each end with a part-spherical knob (lug), two clamps, one for clamping each knob to the handlebar at spaced apart locations, in which respect each clamp comprises two opposing clamp portions, each formed with a part-spherical recess for reception therebetween of the respective crossbrace knob, with

a further recess having a part-circular cross-section for reception therebetween of the handlebar location at which it is to be fitted, and with at least one aperture, and at least one fastener for each clamp, which fastener, in use, engages through the apertures in the opposing clamp portions to clamp them to both the handlebar and the cross brace knob.

In preferred embodiments in accordance with the invention each clamp portion is formed with two apertures, one adjacent each side of the part-spherical recess, and two fasteners are provided for each clamp for engagement through these two apertures in each opposing position of each clamp so as to clamp them to both the handlebar and the crossbrace knob.

The invention will be described further by way of example with reference to the accompanying drawings, in which:

Figure 1 is a perspective view of a known handlebar fitted with a crossbrace, as already described above;

Figure 2 is a fragmentary, enlarged scale, perspective view of a known clamp attaching a crossbrace to a handlebar, as also already described above;

Figure 3 is a side view of a crossbrace, which is a component of a preferred embodiment of a crossbrace clamp assembly of the present invention;

Figure 4 is an exploded perspective view from above showing the clamping of one end of the crossbrace of Figure 3 to a handlebar in accordance with a preferred clamp arrangement of the invention; and

Figure 5 shows the same parts as in Figure 4, but now viewed partially from the front.

Referring to Figures 3 to 5, a preferred practical embodiment of the crossbrace clamp assembly of the invention comprises a crossbrace 30, two clamps 40, only one of which is shown in Figures 4 and 5, as there is one for attaching each end of the crossbrace 30 and the other one corresponds, and respective bolts 50 and nuts 52 for securing the clamps 40.

The crossbrace 30, as shown fully in Figure 3, comprises an aluminium rod which at each end tapers somewhat and is then formed with a terminal, part-spherical knob 32.

Each clamp 40 comprises two opposing clamp portions or jaws 42, 44. Each such jaw 42 or 44 is configured on its surface which, in use, will face the other with a part spherical recess 46 and a further recess 48 which is part-circular in cross-section. As is apparent by reference to Figures 4 and 5, the recesses 48 fit snugly around a handlebar 60, only a small part of which is shown, when the two jaws 42, 44 are connected together. At the

same time the recesses 46 fit closely around and clamp one knob 32 of the crossbrace 30.

Each jaw 42, 44 is also formed with two apertures 41, 43, which are symmetrically located, one adjacent each side of the part-spherical recess 46. These apertures 41, 43 are to enable the clamping together of the jaws 42, 44 by means of the bolts and nuts 50, 52.

When the clamps 40 are intended for fitting to a section of handlebar 60 having a tapered external diameter, as shown in Figures 4 and 5, the recesses 48 will be formed with a corresponding tapering shape so as to be a close fit with a large area of contact. This is to minimise local stress and wear which could in due course lead to or contribute to failure of the bar upon impact. Thus the opposing jaws, 42, 44 may differ in the form of their apertures 41, 43, to accommodate the nuts 52 or the bolts 50 respectively, and in the shape of their recesses 48, in which respect they will substantially mirror symmetrical. The clamp jaws for use at the other end of the crossbrace 30 may also differ in this way so these will usually be four slightly differing jaws for use on a tapered bar.

The advantage of this clamp assembly, particularly the provision of and clamping of the knobs 32 at each end of the crossbrace 30, is that it enables the crossbrace to be fitted

to tapered bars with adequate tightness and maximised contact area notwithstanding the slight differences in taper which may arise between different bars in the manufacturing process.

Moreover, the same clamp jaws will fit equally well to differently sized bars, i.e. bars which are made with different inclination and length of bent sections (see 16, 18 in Figure 1). The provision of knobs 32 ensures that any disposition can be assumed by the crossbrace, without strain, and particularly secure clamping is also ensured.

Other embodiments of the clamp assembly of the invention can be designed for use on non-tapering handlebars i.e. conventional constant external diameter handlebars or stepped diameter handlebars, as described in GB 2321225 and US 6,182,528 and marketed by the applicants under the registered trade mark TWINWALL. In all these cases the recesses (as 48) would simply be of appropriate substantially part-cylindrical shape.

In these and other embodiments, resilient pads, e.g. of rubber, may be provided in the recesses of part-circular cross-section (as 48) between each clamp jaw and the handlebar, for purposes of vibration damping and accuracy of surface contact.

The foregoing is only illustrative of the scope of the invention and other variations in detail are possible in other embodiments. For example, instead of nuts and bolts, other

fasteners could be employed and there is a possibility of employing only a single fastener per clamp.

CLAIMS

1. A crossbrace clamp assembly for a handlebar comprising an elongate crossbrace which is formed at each end with a part-spherical knob (lug), two clamps, one for clamping each knob to the handlebar at spaced apart locations, in which respect each clamp comprises two opposing clamp portions, each formed with a part-spherical recess for reception therebetween of the respective crossbrace knob, with a further recess having a part-circular cross-section for reception therebetween of the handlebar location at which it is to be fitted, and with at least one aperture, and at least one fastener for each clamp, which fastener, in use, engages through the apertures in the opposing clamp portions to clamp them to both the handlebar and the cross brace knob.
2. An assembly as claimed in claim 1 wherein each clamp portion is formed with two apertures, one adjacent each side of the part-spherical recess, and two fasteners are provided for each clamp for engagement through these two apertures in each opposing position of each clamp so as to clamp them to both the handlebar and the crossbrace knob.

3. A motorcycle handlebar fitted with a crossbrace assembly as claimed in claim 1 or 2.
4. A crossbrace clamp assembly substantially as hereinbefore described with reference to and as illustrated in Figures 3 to 5 of the accompanying drawings.

1/2

Fig 1





Fig. 2



